



## DESCRIPTION

The **CBS ArcSafe® RRS-3 DHP/DVP (S)** single-application remote racking system (RRS-3) is designed to operate the Westinghouse Type DHP/DVP (S) circuit breaker without having to make any modifications to existing electrical equipment thanks to CBS ArcSafe's magnetic latching system. The lightweight, portable RRS-3 DHP/DVP (S) allows technicians to remotely install and remove a breaker while standing up to 300 feet away. The RRS-3 DHP/DVP (S) is compatible with Type DHP/DVP circuit breakers with ratings of 1200-2000 A including 50DHP75, 50DHP250, and 50DHP350. Typical applications for the DHP/DVP breaker include electric utility systems, industrial plants, commercial buildings, municipal pumping stations, transportation systems, pipeline stations, and unit substations. Designed, manufactured, and assembled in the USA, all RRS-3 units are portable, fast, and easy to set up, offer mechanical and/or electrical safety protection, are adjustable to fit unique electrical equipment configurations, reduce the requirements for personal protection equipment (PPE), and help customers with NFPA 70E arc-flash safety compliance. Optional features include 25-foot extension cables, 24 V DC LED light, wireless video camera system with LCD monitor, and rugged protective case assembly.



## SPECIFICATIONS

<b>WEIGHT:</b>	28 lbs
<b>DIMENSIONS:</b>	20.0"W x 18.0"H x 13.6"D
<b>POWER CONSUMPTION:</b>	200W
<b>OPERATING DISTANCE:</b>	25-300 feet
<b>COMPATIBILITY:</b>	Type DHP/DVP (S), includes 50DHP75, 1200 A; 50DHP250, 1200-2000 A; 50DHP350, 1200-2000 A
<b>CONTROL/POWER SOURCE:</b>	CBS ArcSafe® RSO-IV control console

## OVERVIEW

- Remote operation from up to 300 feet
- Lightweight, portable, and adjustable
- Simple setup; no equipment modification required
- Reduces or eliminates need for arc-flash hazard suits
- Designed, manufactured, and assembled in the USA

