

## RRS-3 ADVAC (CDP)

ABB ADVAC 1200–3000 A

## DESCRIPTION

The **CBS ArcSafe® RRS-3 ADVAC (CDP)** single-application remote racking solution (RRS-3) is designed to operate the ABB ADVAC vacuum circuit breaker with closed-door racking application featuring interlock pushbutton without having to make any modifications to existing electrical equipment, thanks to CBS ArcSafe's magnetic latching system. The lightweight, portable RRS-3 ADVAC (CDP) allows technicians to remotely install and remove a breaker while standing up to 300 feet away. The RRS-3 ADVAC (CDP) is compatible with all standard 5–15 kV ABB ADVAC circuit breakers featuring closed-door racking with a pushbutton-style interlock. Typical applications for the ABB ADVAC breaker include commercial, industrial, and service entrance applications to protect and switch main, feeders, and incoming lines with continuous ratings of 1200–3000 A. Designed, manufactured, and assembled in the United States, all RRS-3 units are portable, with fast and easy setup. They offer mechanical and/or electrical safety protection, adjust to fit unique electrical equipment configurations, reduce requirements for personal protection equipment, and help customers with NFPA 70E arc-flash safety compliance. Optional features include 25-foot extension cables, 24 V DC LED light, wireless video camera system with LCD monitor, and rugged protective case assembly.

## **SPECIFICATIONS**

WEIGHT:	25 lbs.
DIMENSIONS:	10.8" L x 18" W x 6.2" H
POWER CONSUMPTION:	100 W
OPERATING DISTANCE:	25-300 feet
COMPATIBILITY:	ABB ADVAC vacuum circuit breaker with closed-door racking
CONTROL/POWER SOURCE:	CBS ArcSafe® RSO-IV control console



## **OVERVIEW**

- Remote operation from up to 300 feet away
- · Lightweight and portable for hard-to-access areas
- Simple setup; no equipment modification required
- · Reduces or eliminates need for arc-flash hazard suits
- Designed, manufactured, and assembled in the USA





(472-3389) **(877) 4-SAFETY** 

